



PRIMER 100



Meexe Primer 100 is the right primer for absorbent surfaces such as plaster or plasterboard. It is highly effective due to its depth of penetration and is ready to use.

It is a water-based acrylic dispersion and only one coat needs to be applied by brush or microfibre roller.

PROPERTIES

- Adhesion promoter for absorbent substrates.
- Can be applied by roller or brush in a single coat.
- Water-based, non-flammable.
- Free of plasticisers, solvents, ammonia and emulsifiers.
- The product is supplied ready for use.

CONSUMPTION

Meexe Primer 100 in general has a yield of 0.10 L/m²

SPECIAL PRECAUTIONS

In case of contact with eyes, flush with plenty of water for 15 minutes. In case of contact with skin wash with soap and water. Do not swallow. If swallowed, do not induce vomiting and seek medical attention immediately.

It is recommended to comply with the following measures:

- - Good ventilation
- - Protective goggles to prevent splashing
- - Rubber gloves

Empty containers must be disposed of in accordance with current legislation. To prevent the product from drying out or thickening, close the lid after each use. This product is non-toxic, non-hazardous and non-flammable under normal handling conditions. This product does not contain any harmful substances that would require, under current regulations, any additional labelling measures. Keep out of the reach of children.

TECHNICAL DATA

- Water based acrylic dispersion
- Appearance: Milky liquid
- Solids: 10.7 %
- pH: Between 8 and 9
- Viscosity: 10 - 11s (Copa Ford 4)
- Density at 20°C: 1,01 ± 0,01 g/mL
- Application temperature: 5°C to 35°C
- Touch dry: 30 minutes

APPLICATION

The substrate must be dry, clean and firm, free of grease or oil. Wait a minimum of 30 minutes and no more than 24 hours before applying the first coat of microcement.

PACKAGING

It comes in 5-litre jerrycan.

TOOL CLEANING

Tools are washed with water immediately after use its use.